


T5 HFI WP Stick-Lite Waterproof IP64 lighting

WITH BUILT IN BALLAST, SWITCHED ONLY

- The T5 HFi WP stick-lite now has a 32.5mm diameter with a 1.5mm wall thickness.
- A variety of suspension and mounting clips are available.
- Suitable for indoor and outdoor applications.
- 3m cable supplied with UK or EU plug.
- Extra long power cable without plugs, cost option.
- Waterproof IP64.
- Pressure compensation valve built in.
- Satin outer case as standard.
- Available in all DDP colours.
- No emergency option available.
- No dimmable option, switched only.
- Mounting, fix mounting clips to wall or ceiling approximately 100mm from the ends of the lamp. Do not suspend from power cable, always use suspension kit HFI WP SK.



EncapSulite
Australia





Please note all plastics absorb moisture and this phenomena will produce more condensation in fittings directly exposed to rain for extended periods than those that are not. Please call for more information if required.

T5 HFi WP Stick-Lite

Waterproof IP64 lighting

WITH BUILT IN BALLAST, SWITCHED ONLY

- Tested to IP64.
- Not suitable for immersion.
- Please enquire to verify if this product is suitable for your application.
- Encapsulite will not accept responsibility for products used in unsuitable applications.
- Type X HFi WP, the HFi Stick-lite is supplied with an external plug and cable that if damaged, shall be replaced by a special plug and cable available exclusively from Encapsulite or our service agent.
- Glow wire test 850c.
- AS/NZS CISPR 15:2002  N14710
- Tested to BS4533: 102.1: 1190/EN 60598-2-1: 1989 / BS60598-1: 2008.
- CE WEEE and ROHS compliant.
- 230v 50-60Hz.
- Suitable for mounting on combustible surfaces. 

RE-LAMPING

Disconnect and isolate power supply before commencing any maintenance.
 Unscrew top of cable gland 2 turns.
 Unscrew bottom of cable gland 2 turns.
 Slide end cap out of the end of the tube, (outer case).
 Carefully pull lamp tray out of the tube, (outer case).
 Twist lamp 90 degrees and lift out.
 Fit new lamp and twist 90 degrees only, make sure both ends of lamp are located correctly.
 Slide lamp tray carefully back in to the tube (outer case).
 Slide end cap back in to the end of the tube (outer case).
 Make sure the locator in the end cap sits in the slot at the end of the tube (outer case).
 Tighten the base of the cable gland until a good seal is visible around the outer case.
 Do not overtighten and cause the outer case to distort, as this will cause stress fractures over a period of time.
 Finally tighten the top of the cable gland to seal the cable.

Product Code	Overall Length	Illuminated Length
HFi T5 WP 8w	535mm	270mm
HFi T5 WP 13w	770mm	495mm
HFi T5 WP 14w	795mm	530mm
HFi T5 WP 21w	1105mm	830mm
HFi T5 WP 28w	1400mm	1130mm
HFi T5 WP 35w	1730mm	1430mm

Not suitable for steam rooms/saunas and environments with airborne chemicals. Do not clean with any chemicals, T5 and T8 lamps not suitable for dimming outdoors or below +10°C.



Do not mega test.
Incorrect wiring or programming will invalidate all warranties.

For Product support Freecall 1800 733 113 or Email info@yld.com.au